

K2 Type Wall Mounted



The Wall mounted unit has a stylish smooth panel that looks good and easy to clean

The unit is also smaller, lighter and substantially quieter than previous models making it ideal for small offices and other commercial applications.

Technical focus

- Closed discharge port
- Lighter and smaller units make the installation easy
- Quiet operation
- Smooth and durable design
- Piping outlet in three directions
- Air distribution is automatically altered depending on the operational mode



PAW-RE2C4
Optional Controller.
Control for hotel application.



CZ-RTCSB
Optional Controller.
Wired remote controller.
Compatible with Econavi.



CZ-CENSC1
Optional Econavi Sensor.



CZ-RWS3
Optional Controller.
Infrared remote controller.




CZ-RE2C2
Optional Controller.
Simplified wired remote controller.


Model		S-15MK2E5A	S-22MK2E5A	S-28MK2E5A	S-36MK2E5A	S-45MK2E5A	S-56MK2E5A	S-73MK2E5A	S-106MK2E5A		
Cooling capacity	kW	1,50	2,20	2,80	3,60	4,50	5,60	7,30	10,60		
Input power cooling	W	25,00	25,00	25,00	30,00	30,00	35,00	55,00	80,00		
Operating current cooling	A	0,20	0,21	0,23	0,25	0,32	0,35	0,51	0,70		
Heating capacity	kW	1,70	2,50	3,20	4,20	5,00	6,30	8,00	11,40		
Input power heating	W	25,00	25,00	25,00	30,00	30,00	35,00	55,00	80,00		
Operating current heating	A	0,20	0,21	0,23	0,25	0,32	0,35	0,51	0,70		
Fan type		Cross flow	Cross flow	Cross flow	Cross flow	Cross flow	Cross flow	Cross flow	Cross flow		
Air volume	Cool	m ³ /min	7,90 / 7,40 / 6,50	9,00 / 7,50 / 6,50	9,50 / 8,30 / 6,50	10,90 / 9,00 / 6,50	14,50 / 12,50 / 10,00	16,00 / 14,00 / 12,00	19,50 / 17,00 / 14,00	21,50 / 18,50 / 15,00	
	Hi / Med / Lo	Heat	m ³ /min	9,00 / 7,70 / 6,80	9,20 / 8,30 / 6,80	9,70 / 8,50 / 6,80	11,20 / 9,50 / 6,80	14,50 / 12,50 / 10,00	16,00 / 14,00 / 12,00	19,50 / 17,00 / 14,00	21,50 / 18,50 / 15,00
Sound pressure	Hi / Med / Lo	dB(A)	34 / 32 / 29	36 / 33 / 29	37 / 34 / 29	40 / 36 / 29	38 / 35 / 33	40 / 37 / 35	47 / 44 / 40	49 / 46 / 42	
Sound power	Hi / Med / Lo	dB	49 / 47 / 44	51 / 48 / 44	52 / 49 / 44	55 / 51 / 44	53 / 50 / 48	55 / 52 / 50	62 / 59 / 55	64 / 61 / 57	
Dimension	H x W x D	mm	290 x 870 x 214	290 x 870 x 214	290 x 870 x 214	290 x 870 x 214	302 x 1120 x 236	302 x 1120 x 236	302 x 1120 x 236	302 x 1120 x 236	
Net weight		kg	9	9	9	9	13	13	14	14	
Piping connections	Liquid pipe	Inch (mm)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	1/4 (6,35)	3/8 (9,52)	3/8 (9,52)	
	Gas pipe	Inch (mm)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	1/2 (12,70)	5/8 (15,88)	5/8 (15,88)	

Closed discharge port

When the unit is turned OFF, the flap closes completely to prevent entry of dust into the unit and to keep the equipment clean. Lighter and smaller units make the installation easy. The width has been decreased by 17% and the units are lighter.



Air distribution is automatically altered depending on the operational mode of the unit



Piping outlet in six directions

Piping outlet is possible in the six directions of right, right rear, right bottom, left, left rear and left bottom, making the installation work easier.

Quiet operation

These units are among the quietest in the industry, making them ideal for hotels and hospitals.

External valve (Optional)

CZ-P56SVK2 (model sizes 15 to 56)
CZ-P160SVK2 (model sizes 73 to 106)

